



## Multifunction oven



### CFE 910 CV-GN (GN 1/1) CFE 910 CV-EUR (600 x 400)



Electric oven (convection and steam), 10 x GN 1/1 levels or 600 x 400, 65mm apart.

- Capacity: 10 levels, 65mm apart (grids 600 x 400 mm or GN1/1) or GN1/1 containers, 40mm deep.
- Loading rack: GN 1/1 (910 CV-GN) or 600 x 400 (910 CV- EUR).
- Interior dimensions: L 700 - D 454 - H 728 mm.
- Electromechanical controls.
- Cooking modes: steam, forced convection and multifunction (steam + forced convection).
- Reheating mode (to warm up the prepared plates).
- Thermostat 50/250°C.
- Low-temperature steam cooking (60 - 100°C).
- Safety thermostat;
- Rotation speed control for the oven turbine.
- Cooking temperature thermometer.
- Fast cooling mode for the enclosure.
- Stainless steel side panels and muffle (F18 TNB).
- Double-glazed porthole door (fixed glazing and hinged heat-absorbing glazing).
- Power: 18 kW.
- Power supply: 230 V / 400V + N + E
- Threaded exhaust tube, diam. 1" ½ (40-49 mm).
- Condensation collection gutter (door and oven).
- Cooling of condensates.
- Steam extraction through adjustable air inlet.
- Internal lighting.
- Removable loading rack.

**CFE 910 CV-GN / CFE 910 CV-EUR** L 950 - D 850 - H 995



*The Chief's Choice*